



DRYTREAT

Excellence in sealing products™

INTENSIFIA™

DEEP ENHANCEMENT AND STAIN PROTECTION

Deep, long lasting color enhancement and premium stain protection for porous surfaces, including natural stone, bricks, tiles, pavers, concrete, masonry & terracotta.



- Provides deep color enhancement
- Premium oil and water based stain repellence**
- Easy to apply
- Retards moss, mold and mildew growth
- Breathable: water vapour permeates freely, avoiding moisture build-up inside the material
- Retains wet slip resistance of porous flooring material
- Suitable for indoor, outdoor, residential and commercial use
- 5 year warranty*

*Warranty valid after being applied by an Accredited Applicator – see product label for details.

**Performs better than ISO10545-14 Determination of resistance to stains Class 5 (highest class)



INTENSIFIA™ WILL PROTECT:

Granite	Quarry tiles	Travertine
Limestone	Terrazzo	Basalt
Sandstone	Concrete	Marble
Terracotta tiles	Cement pavers	Slate
Saltillo tiles	Clay pavers	Brick

6 easy steps

ALL YOU WILL NEED:

- INTENSIFIA™
- Low pressure hand spray/lamb's wool applicator/brush
- Protective eyewear
- Gloves
- Sufficient white absorbent cloths / towels



TEST

Test product on a small area of the surface, wait 24 hours, and ensure you are satisfied with the results.



CLEAN

Make sure the area is clean, dry and free of residues or topical coatings.



FIRST COAT

Generously apply INTENSIFIA™ using a lamb's wool applicator/brush/pump spray. Leave the product to penetrate for at least 30 minutes.



REMOVE EXCESS

Thoroughly polish off all residue with clean, dry cotton cloths / towels, then let the product cure for at least an hour.



SECOND COAT

Repeat steps 3 and 4. A third coat may be required for premium stain protection on extremely porous surfaces.



CLEAN REGULARLY

Regularly clean to keep the surface in top condition.



Rejuvenata Active
For Indoors



Oxy-Klenza
For Outdoors



Rejuvenata Spray
For Countertops

Note: Surface can be walked on 2-3 hours after application.
Do not get the surface wet for at least 8-10 hours.

Refer to the product label, full specification sheet and Material Safety Data Sheet (available at www.drytreat.com) for further information, precautions and safety instructions.

Dry-Treat Pty Ltd
St. Leonards, Australia
Ph: 1800 675 119

Dry-Treat Ltd
Leicester, UK
Ph: 0800 096 4760

Dry-Treat Inc.
Wilmington, USA
Ph: 1866 667 5119

www.drytreat.com

info@drytreat.com